

# 5X

Buy the leader, Become the Leader

## The Harves **Boss**



- # high E 1 acre
- # Fuel 71 per hour
- # 1000
- # Excelent





JOIN US

## Specification

5X

		Unit	Specification
Model		/	5X
Structural style		/	Crawler-type full feeding model
Dimension (length*width*height)			5,000×2,530×2,880
Total weight (cabin/canopy)		kg	3,720
Ground clearance		mm	350
Production efficiency		hm <sup>2</sup> / h	0.55 ~ 0.95
Fuel consumption		kg/hm <sup>2</sup>	≤32
Feed quantity		kg/s	6.0
Matching power	Manufacturing factory	/	5K99-V, 102HP
	Structural style	/	4-cylinder, water cool, turbocharge
	Rated power/Max. power	HP	Rated 100HP STAGE II
	rated speed	r/min	2,600
	Fuel Tank capacity	L	160 L
Track	Distance X Section X width <u>Stronger rollers</u>	mm	<u>90mm×56×550mm</u>
	Track distance btw. two guage	mm	<u>1,250</u>
Theory operating speed		km/h	0 ~ 8.2
Reel	Type	/	Eccentric gear type
	Diameter	mm	900
	Plate qty.	↑	5
Cutter bar lifting device type		/	Hydraulic lifting jack cylinders
Cutter width		mm	<u>2200mm</u>
Cutting bar	Type	/	Pin tooth axial flow type
Threshing cylinder	Front thresher	mm	—
Diameter*length	Rear thresher	mm	<u>620×2,210</u>
			<u>FULLY Interchanged</u>
Rethresher type		/	Pin tooth type
Concave grid		/	Sieve type
HST & Gearbox model		/	<u>56HST+95GEARBOX</u>
Grain unloading method		/	360° unloading charge / Lower air filter with cap on grain tank
Grain tank capacity		m <sup>3</sup>	<u>1.6 m<sup>3</sup> New type</u>